

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity

Perma Seel

Alternate Names

Multi-Purpose External Embalming Seal

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

External Embalming Seal

Application Method

See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name

The Dodge Company, Inc.
9 Progress Road
Billerica, MA 01821

Emergency

CHEMTREC (USA)

(800) 424-9300

Customer Service

The Dodge Company, Inc

(800) 443-6343, (978) 600-2099

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 1;H224

Extremely flammable liquid and vapor.

Acute Tox. 4;H302

Harmful if swallowed.

Skin Irrit. 2;H315

Causes skin irritation.

Eye Irrit. 2;H319

Causes serious eye irritation.

Repr. 2;H361D

Suspected of damaging the unborn child.

STOT SE 3;H336

May cause drowsiness or dizziness.

STOT RE 2;H373

May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H224 Extremely flammable liquid and vapor.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+312 IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice / attention.

P314 Get Medical advice / attention if you feel unwell.

P321 Specific treatment (see information on this label).

P330 Rinse mouth.

P337+313 If eye irritation persists: Get medical advice / attention.

P362 Take off contaminated clothing and wash before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Toluene CAS Number: 0000108-88-3	25 - 50	Flam. Liq. 2;H225 Repr. 2;H361d Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336	[1][2]
2-Propanone CAS Number: 0000067-64-1	10 - 25	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Acetic acid, 1-methylethyl ester CAS Number: 0000108-21-4	1.0 - 10	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



4. First aid measures

4.1. Description of first aid measures

General	<p>Move victim to fresh air. Call 911 or emergency medical service if deemed necessary. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. Remove and isolate contaminated clothing and shoes. In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. Wash skin with soap and water. In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. Keep victim warm and quiet. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.</p>
Inhalation	<p>Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.</p>
Eyes	<p>Irrigate copiously with clean fresh water for at least 15 minutes, holding the eyelids apart and seek medical attention.</p>
Skin	<p>Remove and isolate contaminated clothing and shoes. In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. Shower and wash with soap and water. Keep victim warm and quiet.</p>
Ingestion	<p>If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.</p>

4.2. Most important symptoms and effects, both acute and delayed

Overview	<p>Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.</p> <p>Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.</p>
Inhalation	<p>May cause drowsiness or dizziness.</p>
Eyes	<p>Causes serious eye irritation.</p>
Skin	<p>Causes skin irritation.</p>

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



Ingestion

DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get medical attention..

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO², powder, water spray.
Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Carbon Monoxide and Carbon Dioxide
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat / sparks / open flames / hot surfaces - No smoking.
Use explosion-proof electrical / ventilating / light / equipment.
Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).
Structural firefighters' protective clothing will only provide limited protection.
HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
Vapors may form explosive mixtures with air.
Vapors may travel to source of ignition and flash back.
Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
Vapor explosion hazard indoors, outdoors or in sewers.
Runoff to sewer may create fire or explosion hazard.
Containers may explode when heated.
Many liquids are lighter than water.
Substance may be transported hot.
Inhalation or contact with material may irritate or burn skin and eyes.
Fire may produce irritating, corrosive and/or toxic gases.
Vapors may cause dizziness or suffocation.
Runoff from fire control or dilution water may cause pollution.

ERG Guide No. 128

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Vapor is heavier than air and may flow along surface to distant ignition source and flashback.

Large Spill: As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.

Keep unauthorized personnel away.

Stay upwind.

Keep out of low areas.

Ventilate closed spaces before entering.

7. Handling and storage

7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Strong oxidizing agents

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingestion	Source	Value
0000067-64-1	2-Propanone	OSHA	TWA 1000 ppm (2400 mg/m ³) STEL 2400 mg/m ³
		ACGIH	TWA: 250 ppm STEL: 500 ppm Skin
		NIOSH	250 ppm (590 mg/m ³) TWA
		Supplier	No Established Limit
0000108-21-4	Acetic acid, 1-methylethyl ester	OSHA	TWA 250 ppm (950 mg/m ³)
		ACGIH	TWA: 100 ppm STEL: 200 ppm Revised 2003,
		NIOSH	no established RELs
		Supplier	No Established Limit
0000108-88-3	Toluene	OSHA	TWA 200 ppm C 300 ppm 500 ppm (10-minute maximum peak) STEL 150 ppm
		ACGIH	TWA: 20 ppmR
		NIOSH	TWA 100 ppm (375 mg/m ³) ST 150 ppm (560 mg/m ³)
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingestion	Source	Value
0000067-64-1	2-Propanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-21-4	Acetic acid, 1-methylethyl ester	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-88-3	Toluene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

8.2. Exposure controls

Respiratory

Not necessary where area is properly ventilated.

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



Eyes	Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.
Skin	Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Wear PVC or rubber gloves.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Clear Colorless Liquid
Odor	Aromatic Hydrocarbon
Odor threshold	Not Measured
pH	NA
Melting point / freezing point (°C)	NA
Initial boiling point and boiling range (°C)	60C 140F
Flash Point	0C 32F
Evaporation rate (Ether = 1)	> 1 (n-Butyl acetate = 1)
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1% Upper Explosive Limit: 12.8%
Vapor pressure (Pa)	Not Measured
Vapor Density	Greater than 1
Specific Gravity	0.950-0.970
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature (°C)	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC %	54%

9.2. Other information

No other relevant information.

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid contact with open flame, sparks or hot surfaces.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Carbon Monoxide and Carbon Dioxide

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

2-butoxyethanol and its acetate are readily absorbed through the skin and will cause harmful effects on the blood.

Safety Data Sheet

Perma Seal

SDS Revision Date:

03/14/2014



Safety Data Sheet

Perma Seal

SDS Revision Date:

03/14/2014



Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Toluene - (108-88-3)	636.00, Rat - Category: 4	8,400.00, Rabbit - Category: NA	No data available	No data available	No data available
2-Propanone - (67-64-1)	2,000.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	76.00, Rat - Category: NA	No data available	No data available
Acetic acid, 1-methylethyl ester - (108-21-4)	6,750.00, Rat - Category: NA	20,000.00, Rabbit - Category: NA	17,129.60, Rabbit - Category: NA	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	4	Harmful if swallowed.
Acute Toxicity (skin)	---	Not Applicable
Acute Toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)	---	Not Applicable
Sensitization (skin)	---	Not Applicable
Germ toxicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive Toxicity	Not Defined	Suspected of damaging the unborn child.
Specific target organ systemic toxicity (single exposure)	3	May cause drowsiness or dizziness.
Specific target organ systemic Toxicity (repeated exposure)	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

Safety Data Sheet

Perma Seal

SDS Revision Date:

03/14/2014



12. Ecological information

12.1. Toxicity

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Toluene - (108-88-3)	5.80, Oncorhynchus mykiss	19.60, Daphnia magna	Not Available
2-Propanone - (67-64-1)	100.00, Pimephales promelas	10.00, Daphnia magna	20.565 (72 hr), Ulva pertusa
Acetic acid, 1-methylethyl ester - (108-21-4)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

14. Transport information

- 14.1. UN number** UN1993
14.2. UN proper shipping name Flammable liquids, n.o.s. (Contains Toluene/Acetone)
14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)

DOT Proper Shipping Name UN1993, Flammable liquids, n.o.s. (Contains Toluene/Acetone), 3, III
DOT Hazard Class 3
DOT Label 3
UN / NA Number UN1993
DOT Packing Group III
CERCLA/DOT RQ 267 gal. / 2222 lbs.

IMO / IMDG (Ocean Transportation)

IMDG Proper Shipping Name Flammable liquids, n.o.s. (Contains Toluene/Acetone)
IMDG Hazard Class Sub Class 3 Not Applicable
IMDG Packing Group III

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2 D2A

US EPA Tier II Hazards

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes

Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs (lbs):

2-Propanone (5,000.00)

Toluene (1,000.00)

EPCRA 302 Extremely Hazardous :

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals:

Toluene

Proposition 65 - Carcinogens (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):

Toluene

Proposition 65 - Female Repro Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):

(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

Acetic acid, 1-methylethyl ester

2-Propanone

Toluene

Penn RTK Substances (>1%) :

Acetic acid, 1-methylethyl ester

Safety Data Sheet

Perma Seel

SDS Revision Date:

03/14/2014



2-Propanone

Toluene

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H305 May be harmful if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H320 Causes eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H360 May damage fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child.

H362 May cause harm to breast-fed children.

H370 Causes damage to organs.

H371 May cause damage to organs.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

This is the first revision of this SDS format, changes from previous revision not applicable.

Safety Data Sheet

Perma Seal

SDS Revision Date:

03/14/2014



This Safety data Sheet was prepared using information provided by/obtained from the Dodge Chemical Company Inc. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to the product. The Dodge Chemical Company, Inc. expressly disclaim all expressed or implied warranty and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other processes as to the accuracy of and/or sufficiency of such information. This Safety Data Sheet may not be changed or altered in any way without the expressed knowledge and permission of The Dodge Chemical Company, Inc.

End of Document